

# BLACKHAWK HP™



## COMMERCIAL

### MODELS:

2454KW 23.5hp, 54" Deck

2460KW 23.5hp, 60" Deck

2660KWE 26hp, 60" Deck



BlackHawk HP 2460KW shown\*

## WHERE COMMERCIAL MEETS COMFORTABLE.

The **BlackHawk HP** provides the superior mowing experience with advanced operator controls, commercial grade components, and best-in-class performance and comfort.

- **Total Comfort** – Full suspension with padded design provides lateral stability and comfort.
- **Foot-Operated OCDC** – A foot-operated OCDC (operator-controlled discharge chute) allows you to keep your hands on the steering levers while closing the discharge chute on the fly.
- **Proven Power** – Equipped with the industry preferred Kawasaki® FX or FT EFI engines for reliability and performance year after year.
- **Smoothest Steering** – The Parker® HTJ series transmissions offer super smooth steering up to 10 miles per hour in a compact, quiet, and efficient drivetrain.
- **Robust Deck** – Offered in two cutting widths (54" and 60"), the BlackHawk HP deck features a deep 7 gauge shell and abrasion resistance baffles to outlast the competition in extreme conditions.
- **Peer® Turf Xtreme™ Spindles** – Maintenance free and constructed of high-strength ductile iron.




**Suspension Seat** – Full suspension for ultimate comfort all day long.




**OCDC** – Foot-operated to keep your hands on the steering levers



**Parker® HTJ** – Smooth steering and speeds up to 10 miles per hour



**Kawasaki® Engines** – Reliable power to tackle the toughest jobs



**54" and 60" Decks** – Deep 7 gauge shell to tackle deep grass with ease

**3 YEAR  
BUMPER-TO-BUMPER  
WARRANTY\***

\*Unlimited hour limited warranty, see dealer for complete warranty details

# BLACKHAWK HP™



	54" Deck	60" Deck	
Model	2454KW	2460KW	2660KWE
<b>Engine</b>			
Manufacturer	Kawasaki® FX		Kawasaki® FT EFI
Horsepower	23.5		26
Displacement	726cc		
Air-cleaner	4 stage		Vortical Air Filtration
Cooling	Air-cooled		
Starter	Electric		
Engine warranty	3-Year		

<b>Drive System</b>			
Dual hydrostatic	Parker® HTJ		
Ground speed	10 mph		
Parking brake	Integrated in transaxle		
Towing capacity	200 lbs		

Mower Deck		
Deck size	54"	60"
Acres/hour*	4.3	4.8
Cutting height	1" - 5"	
OCDC (operator controlled discharge chute)	Foot-operated (standard)	
Deck height adjustments	Manual lift, 1/4" increments	
Electric lift	Optional	
Deck engagement	Ogura® 150 ft-lb	
Construction	7 ga formed & welded, Abrasion Resistance Baffles	
Blades	(3) - 2.5" x 19"	(3) - 2.5" x 20.5"
Blade tip speed (approximate)	18,500 fpm	
Spindles	1.25" effective diameter machined shaft	
Spindle housings	Peer® Turf Xtreme™ ductile iron (sealed)	
Anti-scalp rollers	4	
Pulleys	7 ga vented split steel deep groove	

<b>General</b>			
Battery	12 Volt, 350cca		
Digital Display	Tachometer, hour meter, fuel gauge		
Fuel capacity	7 gallons		
Rear tires	23 x 10.5-12 GrassMaster		
Front tires	13 x 6.5-6		
Frame	Welded C-channel, 7 ga formed		
Floor-pan	Removable, steel		
Seat	Full suspension, adjustable seat w/ armrests		
Springer Forks	Optional accessory		

Dimensions		
Overall height (rollbar down)	50"	
Overall height (rollbar up)	71"	
Overall width (chute down)	69.6"	76"
Overall width (chute up)	55.4"	61.9"
Overall length (rollbar down)	85.8"	
Overall length (rollbar up)	81.3"	
Weight	1132 lbs	1140 lbs