

BLACKHAWK™

COMMERCIAL



MODELS:

2448KW 24hp, 48" Deck

2454KW 24hp, 54" Deck

2460KW 24hp, 60" Deck



BlackHawk 2460KW shown*

THE SMOOTHEST DRIVING MOWER ON THE MARKET.

The **BlackHawk** is built to redefine your mowing experience with superior value, advanced operator controls, commercial grade components, and unmatched performance.

- **Foot-Operated OCDC** – Our foot-operated OCDC (operator-controlled discharge chute) allows you to keep your hands on the steering levers while closing the discharge chute on the fly.
- **Proven Power** – Equipped with 24 horsepower Kawasaki® FS engines for trusted reliability and performance.
- **Robust Deck** – Offered in three cutting widths (48", 54" and 60"), the BlackHawk deck features a deep 7 gauge shell and abrasion resistance baffles to outlast the competition in extreme conditions.
- **Smoothest Steering** – The Parker® HTE series transmissions offer super smooth steering up to 9 miles per hour in a compact, quiet, and efficient drivetrain.
- **Total Comfort** – The padded and over-sized bolstered seat hugs your torso for ultimate comfort.
- **Peer® Turf Xtreme™ Spindles** – Maintenance free and constructed of high-strength ductile iron.



OCDC – Foot-operated to keep your hands on the steering levers



Hitch Receiver – Class 1 hitch for easier mounting of accessories



Parker® HTE – Smooth steering and 1,000 hour oil change intervals



PEER® Spindles – Maintenance free with Contamination Exclusion Technology



48", 54", and 60" Decks – Deep 7 gauge shell to tackle deep grass with ease

**3 YEAR
BUMPER-TO-BUMPER
WARRANTY***

*Unlimited hour limited warranty, see dealer for complete warranty details



BLACK HAWK™

	48" Deck	54" Deck	60" Deck
Model	2448KW	2454KW	2460KW
Engine			
Manufacturer	Kawasaki® FS		
Horsepower	24		
Displacement	726cc		
Air-cleaner	2 stage		
Cooling	Air-cooled		
Starter	Electric		
Engine warranty	3-Year		

Drive System			
Dual hydrostatic	Parker® HTE		
Ground speed	9 mph		
Parking brake	Integrated in transaxle		
Towing capacity	200 lbs		

Mower Deck			
Deck size	48"	54"	60"
Acres/hour*	3.4	3.9	4.3
Cutting height	1" - 5"		
OCD (operator controlled discharge chute)	Foot-operated (standard)		
Deck height adjustments	Manual lift, 1/4" increments		
Electric lift	Optional		
Deck engagement	Ogura® 150 ft-lbs		
Construction	7 ga formed & welded, Abrasion Resistance Baffles		
Blades	(3) -2.5" x 17.25"	(3) - 2.5" x 19"	(3) - 2.5" x 20.5"
Blade tip speed (approximate)	18,500 fpm		
Spindles	1.25" effective diameter machined shaft		
Spindle housings	Peer® Turf Xtreme™ ductile iron (sealed)		
Anti-scalp rollers	4		
Pulleys	7 ga steel deep groove		Vented split 3/8" steel deep groove

General			
Battery	12 Volt, 350cca		
Digital Display	Tachometer, hour meter, fuel gauge		
Fuel capacity	7 gallons		
Rear tires	23 x 10.5-12 GrassMaster		
Front tires	13 x 6.5-6		
Frame	Welded C-channel, 7 ga formed		
Floor-pan	Removable, steel		
Seat	24" high-back adjustable padded seat w/ armrests		
Springer Forks	Optional accessory		

Dimensions			
Overall height (rollbar down)	50"		
Overall height (rollbar up)	71"		
Overall width (chute down)	63.6"	69.6"	76"
Overall width (chute up)	49.2"	55.4"	61.9"
Overall length (rollbar down)	85.8"		
Overall length (rollbar up)	81.3"		
Weight	1104 lbs	1114 lbs	1121 lbs