

EAGLE

COMMERCIAL

MODELS:

2754KW 27hp, 54" Deck

2760KW 27hp, 60" Deck




Eagle 2754KW shown*

LADIES AND GENTLEMEN, THE EAGLE HAS LANDED.

The **Eagle** is loaded with commercial features and delivers more speed, power, and performance to maintain your home's property, commercial accounts, and everything in between.

- **Foot-Operated OCDC** – A foot-operated OCDC (operator-controlled discharge chute) allows you to take full control of your clippings.
- **Proven Power** – Equipped with the industry preferred Kawasaki® FX engine for trusted reliability and performance.
- **Robust Deck** – Offered in two cutting widths (54" and 60"), the Eagle's deck features a deep 7 gauge shell and abrasion resistance baffles to outlast the competition in extreme conditions.
- **Smooth AND Fast** – The Parker® HTG series transmissions deliver a smooth drive up to 12 miles per hour in a reliable and efficient drivetrain.
- **Enhanced Comfort** – Full suspension with a padded design and isolated platform provides ultimate comfort.
- **Run-Flat Tires** – Flat tires are a problem of the past with run-flat tires standard on the Eagle.



OCDC – Foot-operated to keep your hands on the steering levers



Ultimate Comfort – ISO mounted suspension seat for all-day comfort



Parker® HTG – Smooth steering and 1,000 hour oil change intervals



Turbinator® Pre-Cleaner – Exclusive feature removes debris for cleaner air



54" and 60" Decks – Deep 7 gauge shell to tackle deep grass with ease

**3 YEAR
BUMPER-TO-BUMPER
WARRANTY***

*Unlimited hour limited warranty, see dealer for complete warranty details.



EAGLE

	54" Deck	60" Deck
Model	2754KW	2760KW
Engine		
Manufacturer	Kawasaki® FX	
Horsepower	27	
Displacement	852cc	
Air-cleaner	4 stage & Turbinator® Pre-Cleaner	
Cooling	Air-cooled	
Starter	Electric	
Engine warranty	3-Year	

Drive System		
Dual hydrostatic	Parker® HTG (14cc)	
Ground speed	12 mph	
Parking brake	Integrated in transaxle	
Towing capacity	1,000 lbs	

Mower Deck		
Deck size	54"	60"
Acres/hour	5.2	5.8
Cutting height	1" - 5"	
OCD (operator controlled discharge chute)	Foot-operated (standard)	
Deck height adjustments	Manual lift, 1/4" increments	
Electric lift	Optional	
Deck engagement	Warner® 250 ft-lbs	
Construction	7 ga formed & welded, Abrasion Resistance Baffles	
Blades	(3) - 2.5" x 19"	(3) - 2.5" x 20.5"
Blade tip speed (approximate)	18,500 fpm	
Spindles	1.25" effective diameter machined shaft	
Spindle housings	Peer® Turf Xtreme™ ductile iron (sealed)	
Anti-scalp rollers	4	
Pulleys	7 ga steel deep groove	Vented split 3/8" steel deep groove

General		
Battery	12 Volt, 350cca	
Digital Display	Tachometer, hour meter, fuel gauge	
Fuel capacity	8 gallons	
Rear tires	25 x 12-12 GrassMaster	
Front tires		
Frame	Welded C-channel, 7 ga formed	
Floor-pan	Removable, steel	
Seat	Full suspension, adjustable seat w/ armrests and isolated platform	
Springer Forks	Optional	

Dimensions		
Overall height (rollbar down)	52.7"	
Overall height (rollbar up)	77.7"	
Overall width (chute down)	70.3"	76.9"
Overall width (chute up)	59.6"	66.1"
Overall length (rollbar down)	88.5"	
Overall length (rollbar up)	84.6"	
Weight	1306 lbs	1322 lbs