

XCALIBER™



INDUSTRIAL

MODELS:

3366KOE 33hp, 66" Deck

3566KW 35hp, 66" Deck

3574KW 35hp, 74" Deck

3574KOE 35hp, 74" Deck



XCaliber 3566KW shown*

THE TOUGHEST MOWER IN THE ZERO-TURN INDUSTRY.

Professional commercial contractors and large property home owners have come to depend on the **XCaliber** for its legendary performance. Our flagship mower features:


- **Pure Power** – Models powered with Kawasaki® FX or fuel efficient Kohler® EFI engines.
- **X2 Wind Tunnel Deck** – The industry's best cutting deck available in 66" and 74" cutting widths for maximum productivity, while retaining the Wind Tunnel design and industry leading 2-inch blade overlap.
- **Comfort Package** – A high-back suspension seat and unique Springer Forks provide a comfortable ride for the operator day in and day out.
- **Productivity** – Our heavy-duty drivetrain of pumps and wheel motors increases ground speed up to 13 mph to mow over 7 acres per hour.
- **Wide Wheelbase** – An extra wide wheelbase assists in hillside performance and overall ride quality.
- **Most Lifetime Warranties** – Worry-free lifetime warranties on the frame, stainless steel, front forks, steering levers, and front caster bearings.



Total Comfort – Suspension seat with recline, lumbar, and padded armrests.



Springer Forks – Absorb bumps for added comfort and increased productivity.



Pumps & Wheel Motors – Guaranteed for 5 years or 3,000 hours.



Turbinator® Pre-Cleaner – Exclusive feature removes debris for cleaner air.



X2 "Wind Tunnel" Deck – Increases airflow and reduces build-up inside deck.

**3 YEAR
BUMPER-TO-BUMPER
WARRANTY***

*Unlimited hour limited warranty, see dealer for complete warranty details.



X-CALIBER™

	66" Deck		74" Deck	
Model	3366KOE	3566KW	3574KW	3574KOE
Engine				
Manufacturer	Kohler® EFI		Kawasaki® FX	
Horsepower	33		35	
Displacement	824cc		999cc	
Air-cleaner	4 stage		4 stage & Turbinator® Pre-Cleaner	
Cooling	Air-cooled			
Starter	Electric			
Engine warranty	3-Year			
Drive System				
Pumps	Hydro-Gear® 21cc			
Wheel motors	Parker® DG335			
Ground speed	13 mph			
Parking brake	Automotive Style			
Towing capacity	2,000 lbs			
Mower Deck				
Deck size	66"		74"	
Acres/hour*	6.9		7.8	
Cutting height	1.25" - 5"			
OCDC (operator controlled discharge chute)	Standard			
Deck height adjustments	Manual lift, 1/4" increments			
Electric lift	Optional			
Deck engagement	Ogura® 250 ft-lbs			
Construction	7 ga formed & welded			
Top plate	7 ga bolted (not welded)			
Blades	3 - 23.3" x 2.5"		3 - 26" x 2.5"	
Blade tip speed (approximate)	18,000 fpm			
Spindle housings	Peer® Turf Xtreme™ ductile iron (sealed)			
Spindles	1.25" effective diameter machined shaft			
Anti-scalp rollers	6			
Spindle cooling fans	Standard (3)			
Pulleys	Vented split 3/16" steel deep groove			
General				
Battery	12 Volt, 350cca			
Digital display	Tachometer, hour meter, voltmeter, service alerts			
Fuel capacity	12 gallons			
Rear tires	25 x 12-12 GrassMaster			
Front tires	15 x 6-8 15 x 6-8 (run-flat)			
Frame	Welded 1" x 2" tube, 7 ga formed			
Fenders	Stainless steel			
Floor-pan	Removable, steel			
Seat	High-back, full suspension, lumbar, recline, and padded armrests			
Springer Forks	Standard			
Dimensions				
Overall height	52"		53"	
Overall height (rollbar up)	77.5"			
Overall width	72"		76"	
Overall length	85"		86"	
Overall length (rollbar down)	88.5"		89.5"	
Weight	1445 lbs		1482 lbs	