

## THE MOWER WITH MORE MUSCLE FOR YOUR MONEY.

- **High Horsepower** A 23 horsepower engine from Kawasaki® or Kohler® to power through thick grass up to 3.1 acres per hour.
- Elite Cutting System Offered in three cutting widths (42", 48", and 54"), the Elite Deck easily cuts large volumes of grass and provides an attractive after-cut appearance.
- **7-Stage Deck Height** Allows you to quickly and easily adjust mowing height for different applications.
- Hydro-Gear® ZT-2800 Transaxles Proven and reliable transmissions with an external oil filter for easier maintenance and extended system life.
- Quick-Lift Lock Allows you to quickly raise the deck to avoid objects and locks the deck in travel height for transporting or storing.
- **Motorcycle Tires** Low profile tires with motorcycle tread provide smoother caster turns.
- **Industry Leading Warranty** Enjoy peace-of-mind with three years of warranty with unlimited hours of residential use and the industry leading lifetime warranties.



**Stainless Steel** – Protects fuel tank from sun and impact damage



**Hydro-Gear® ZT-2800** – Smooth operation and fully serviceable



**42", 48", and 54" Elite Cutting System –** Formed and welded 10 ga deck shell



**Commercial Forks** – Greaseable and lifetime warranty against breakage



**Comfort Ride** – Plush cushioned seat with armrests for extra comfort



\*Unlimited hour limited residential warranty, see dealer for complete warranty details



	42" Deck	48" Deck		54" Deck	
Model	2342KO	2348KO	2348KW	2354KO	2354KW
Engine					
Manufacturer	Kohler® 7000		Kawasaki® FR	Kohler® 7000	Kawasaki® FR
Horsepower	23				
Displacement	724cc		726cc	724cc	726cc
Air-cleaner	2 stage				
Cooling	Air-cooled				
Starter	Electric				
Engine warranty	3-Year				

<b>Drive System</b>	
Dual hydrostatic	Hydro-Gear® ZT-2800 transaxles (internal expansion tank)
Ground speed	7 mph
Parking brake	Integrated in transaxle
Towing capacity	100 lbs

Mower Deck				
Deck size	42 "	48 "	54"	
Acres/hour*	2.4	2.7	3.1	
Cutting height	1.5" - 4.5"			
Deck height adjustments	Manual lift, 1/2" increments			
Deck Quick-Lift	Integrated			
Deck engagement	Ogura® 87 ft-lbs			
Construction	10 ga formed & welded			
Blades	3 - 15.25" x 2.5"	3 - 17.25" x 2.5"	3 - 19.25" x 2.5"	
Blade tip speed (approximate)	18,500 fpm			
Spindles	.75" effective diameter machined shaft			
Spindle housings	1pc keyless sealed cast aluminum			
Anti-scalp rollers	4			
Pulleys	Vented split 3/16" steel deep groove			

General			
Battery	12 Volt, 300cca		
Digital display	hour meter		
Fuel capacity	4 gallons		
Rear tires	20 x 8-10 GrassMaster	20 x 10-8 GrassMaster	
Front tires	13 x 6.5-6		
Frame	Welded 1" x 2", 2" x 2" tube, 10 ga formed		
Fenders	Stainless steel		
Floor-pan	Removable, steel		
Seat	20" padded seat w/ armrests		

Dimensions				
Overall height	47"			
Overall width (with chute)	51.5"	57.5"	64"	
Overall length	76"			
Weight	730 lbs	750 lbs	763 lbs	

