

CLASSIC™

INDUSTRIAL



MODELS:

2750KW 27hp, 50" Deck

2760KW 27hp, 60" Deck

3360KOE 33hp, 60" Deck

3560KW 35hp, 60" Deck

3572KW 35hp, 72" Deck

3572KOE 35hp, 72" Deck



Classic 2760KW shown*

A TRUE CLASSIC AMERICAN WORKHORSE.

The **Classic** is the perfect definition of a workhorse with the combination of commercial quality with industrial features.

- **Power and More Power** – Powered by Kawasaki® FX or Kohler® EFI engines up to 35 horsepower to power through the tough jobs with ease.
- **Lifetime Warranty Frame** – The strongest frame in the industry with a 1" x 2" 7 gauge steel construction guaranteed not to break.
- **Over-Sized Hydraulics** – Reduces the system pressure and backed with a 5-year/3,000 hour warranty.
- **Complete Discharge Control** – An operator controlled discharge chute (OCDC) allows you to switch from normal discharge to closing the chute on the fly.
- **Tried and True Decks** – Offered in three diverse deck widths (50", 60", and 72") the Elite X Deck has been the staple piece to Dixie Chopper's reputation of cleanly cutting all types of grass.
- **Comfort Package** – Our suspension seat and unique Springer Forks comes standard on select Classic models to provide a smooth ride in all terrain.




High Performance Package – Comes standard on select models.



Pumps & Wheel Motors – Stronger transmissions for extended system life.



Spindle Package – Maintenance-free spindles and cooling fans come standard.



50", 60", and 72" Elite X Deck – Gives a quality cut in all types of grass

**3 YEAR
BUMPER-TO-BUMPER
WARRANTY***

*Unlimited hour limited warranty, see dealer for complete warranty details.



CLASSIC™

	50" Deck		60" Deck		72" Deck	
Model	2750KW	2760KW	3360KOE	3560KW	3572KW	3572KOE
Engine						
Manufacturer	Kawasaki® FX		Kohler® EFI	Kawasaki® FX		Kohler® EFI
Horsepower	27		33	35		
Displacement	852cc		824cc	999cc		
Air-cleaner	4 stage & Turbinator® Pre-Cleaner		4 stage	4 stage & Turbinator® Pre-Cleaner		4 stage
Cooling	Air-cooled					
Starter	Electric					
Engine warranty	3-Year					

Drive System						
Pumps	Hydro-Gear® 16cc				Hydro-Gear® 21cc	
Wheel motors	Parker® DG280				Parker® DG335	
Ground speed	12 mph				13 mph	
Parking brake	Automotive Style					
Towing capacity	2,000 lbs					

Mower Deck						
Deck size	50"		60"		72"	
Acres/hour*	4.8		5.8		7.5	
Cutting height	1.25" - 5"					
OCD (operator controlled discharge chute)	Standard					
Deck height adjustments	Manual lift, 1/4" increments					
Electric lift	Optional					
Deck engagement	Ogura® 250 ft-lbs					
Construction	10 ga formed & welded				7 ga formed & welded	
Top plate	7 ga bolted (not welded)					
Blades	3 - 17" x 2.5"		3 - 20.5" x 2.5"		3 - 24" x 2.5"	
Blade tip speed (approximate)	18,000 fpm					
Spindles	1.25" effective diameter machined shaft					
Spindle housings	Peer® Turf Xtreme™ ductile iron (sealed)					
Spindle cooling fans	Standard (3)					
Anti-scalp rollers	4				5	
Pulleys	Vented split 3/16" steel deep groove					

General						
Battery	12 Volt, 350cca					
Digital display	Tachometer, hour meter, voltmeter, service alerts					
Fuel capacity	8 gallons		10 gallons		12 gallons	
Rear tires	25 x 12-12 GrassMaster					
Front tires	15 x 6-8 15 x 6-8 (run-flat)					
Frame	Welded 1" x 2" tube, 7 ga formed					
Fenders	Stainless steel					
Floor-pan	Removable, steel					
Seat	Full suspension, adjustable seat w/ armrests					
Springer Forks	Optional			Standard		

Dimensions						
Overall height	53"					
Overall height (rollbar up)	78"					
Overall width	55.5"		65.5"		76"	
Overall length	77.5"		78"		79"	
Overall length (rollbar down)	81"				83"	
Weight	1074 lbs		1134 lbs		1228 lbs	